



RECALIBRATION PRICE SCHEDULE

APRIL 16, 2008

INSTRUMENTS

In ohms, except 3312A is in °C

<u>MODEL (S)</u>		<u>MODEL (S)</u>	
4201 & 4201C	\$145.00	4221 & 4221C	\$225.00
4202 & 4202C	\$175.00	4312A	\$175.00
4212 & 4212C	\$175.00	3312A	\$175.00
4101A	\$120.00		
AS FOUND ONLY, (6 to 9 POINTS) . . .	\$ 40.00		

RTD SENSORS

(ALL MODELS)

100Ω PLAT.

RANGE 151 -40 to +250°C	\$160.00	RANGE 157 -40 to +500°C	\$245.00
RANGE 152 -100 to +250°C	\$240.00	RANGE 158 -100 to +500°C	\$325.00
RANGE 153 -100 to +400°C	\$280.00	RANGE 159 -200 to +500°C	\$385.00
RANGE 154 -40 to +400°C	\$200.00	RANGE 160 -200 to +250°C	\$300.00
RANGE 155 -40 to +400°C	\$240.00	RANGE 161 -200 to +400°C	\$380.00
RANGE 156 -100 to +400°C	\$320.00	*RANGE 059 -60 to +300°C	\$195.00

*For Model 4101A Only

10% DISCOUNT FOR 3 OR MORE IDENTICAL SENSORS CALIBRATED AT THE SAME TEMPERATURE(S)

-40°C SUPPLIED AS AN EXTRAPOLATION

SENSOR DOCUMENTATION INCLUDES R vs T PRINTOUT AND ITS90 COEFFICIENTS

SYSTEM CHECK

AS FOUND AS LEFT DATA (INSTRUMENT & ONE SENSOR) AT 0 & +100°C	\$60.00
EACH ADDITIONAL SENSOR	\$15.00
EACH ADDITIONAL POSITIVE TEMPERATURE	\$40.00
NEGATIVE TEMPERATURES (-1°C to -70°C) FIRST \$60.00 EA.ADD'L	\$20.00
NEGATIVE TEMPERATURE (-196°C)	\$60.00

THERMISTORS SENSORS

RANGE 031 0 to +70°C	\$140.00
RANGE 030 0 to +100°C	\$150.00
SPOT CALIBRATION (ONE TEMPERATURE).	\$ 45.00

CALIBRATION RESISTOR CARDS

332C (all values) For 4200 Series	\$135.00
33-0366 (2 resistors) For Model 3312A	\$160.00
43-0366 (2 resistors) For Model 4312A	\$160.00

ADDITIONAL INSTRULAB CALIBRATION CAPABILITIES

Instrulab has the capability to calibrate products by other manufacturers

Including:

- Liquid in glass & dial type thermometers and thermistors in the range of -70 to $+400^{\circ}\text{C}$
- Thermocouples in the range of -200 to $+2000^{\circ}\text{F}$
- Also Platinum RTD, Thermistor and Thermocouple actuated instruments

For details, call Mike Lala at 800-241-2241.

NORMAL TURN AROUND TIME IS 2-3 WEEKS

ALL CALIBRATION SUPPLIED WITH "REPORTS OF CALIBRATION" LISTING (WHEN APPLICABLE),
VALUES, TOLERANCES, AND $k=2$ UNCERTAINTIES
ALL CALIBRATIONS ARE TRACEABLE TO NIST (ITS90)
